

IN THE CLAIMS

Please amend claims 1, 2, 5, 9, 10, 13, 16, 17, 18, and 20 as follows:

1. (CURRENTLY AMENDED) A method for managing memory, comprising:  
breaking up a file into two or more memory blocks;  
managing the two or more memory blocks as nodes in a heap tree wherein each node has a  
heap block reference; and  
~~independently compressing one or more of the two or more memory blocks without~~  
~~reprocessing the file.~~  
~~receiving a request to access memory at a linear file address; and~~  
~~translating the linear file address to an appropriate heap block reference to access the~~  
~~memory block.~~

2. (CURRENTLY AMENDED) The method of claim 1, ~~wherein further comprising:~~  
~~receiving a request to access memory at a linear file address; and~~  
~~translating the linear file address to an appropriate heap block reference to access the~~  
~~memory block, wherein the translating utilizes a file address mapping tree comprising a mapping~~  
~~from linear file addresses to heap block references.~~

3. (ORIGINAL) The method of claim 2, further comprising updating the file address  
mapping tree when a block is inserted into the heap tree.

4. (ORIGINAL) The method of claim 2, further comprising updating the file address  
mapping tree when address space is deleted by:

deleting an associated block from the heap tree;  
reducing a size of partial blocks as needed; and  
adjusting the file address mapping tree accordingly.

## BEST AVAILABLE COPY

5. (CURRENTLY AMENDED) The method of claim 2~~4~~, wherein:
- (a) the request to access memory comprises a request to insert data into the file at an insertion point; and
  - (b) the method further comprises:
    - (i) breaking one of the memory blocks at the insertion point; and
    - (ii) inserting the new data as a node in the heap tree.
6. (WITHDRAWN) A method for allocating memory comprising:
- maintaining, in a tree, a tri-linked list of deallocated memory units available for use by a heap, wherein a first link points to available deallocated memory units smaller than a current block size, a second link points to available deallocated memory units equal to the current block size, and a third link points to available deallocated memory units larger than the current block size;
- receiving a request for memory;
- traversing the tree to find a deallocated memory unit that satisfies the request for memory;
- and
- allocating the deallocated memory unit that satisfies the request.
7. (WITHDRAWN) The method of claim 6, wherein the traversing does not search the second link.
8. (WITHDRAWN) The method of claim 6, wherein memory units of equal size are linked together in the tree.
9. (CURRENTLY AMENDED) A system for managing memory comprising:
- (a) a file broken up into two or more blocks of memory;
  - (b) a heap tree configured to manage the two or more blocks of memory as nodes in the heap tree, wherein: one or more of the two or more blocks of memory are independently compressed without reprocessing the file.
- ~~(i) each node has a heap block reference;~~

~~(ii) the heap tree is configured to receive a request to access memory at a linear file address; and~~

~~(iii) the heap tree is configured to translate the linear file address to an appropriate heap block reference to access the memory block.~~

10. (CURRENTLY AMENDED) The system of claim 9, wherein:

(i) each node has a heap block reference;

(ii) the heap tree is configured to receive a request to access memory at a linear file address; and

(iii) the heap tree is configured to translate the linear file address to an appropriate heap block reference to access the memory block; and wherein the system further comprising comprises a file address mapping tree utilized by the heap tree, wherein the file address mapping tree comprises a mapping from linear file addresses to heap block references.

11. (ORIGINAL) The system of claim 10, wherein the file address mapping tree is updated when a block is inserted into the heap tree.

12. (ORIGINAL) The system of claim 10, wherein the file address mapping tree is updated when address space is deleted by:

deleting an associated block from the heap tree;  
reducing a size of partial blocks as needed; and  
adjusting the file address mapping tree accordingly.

13. (CURRENTLY AMENDED) The system of claim 109, wherein:

(a) the request to access memory comprises a request to insert data into the file at an insertion point; and

(b) the heap tree is configured to insert the data by:

(i) breaking one of the memory blocks at the insertion point; and  
(ii) inserting the new data as a node in the heap tree.

14. (WITHDRAWN) A system for allocating memory comprising:
- (a) a heap tree comprising a tri-linked list of deallocated memory units available for use by a heap;
  - (b) a first link of the tri-linked list pointing to available deallocated memory units smaller than a current block size;
  - (c) a second link of the tri-linked list pointing to available deallocated memory units equal to the current block size;
  - (d) a third link of the tri-linked list pointing to available deallocated memory units larger than the current block size;
  - (e) the heap configured to:
    - (i) receive a request for memory;
    - (ii) traverse the heap tree to find a deallocated memory unit that satisfies the request for memory; and
    - (iii) allocate the deallocated memory unit that satisfies the request.

15. (WITHDRAWN) The system of claim 14, wherein memory units of equal size are linked together in the heap tree.

16. (CURRENTLY AMENDED) An article of manufacture comprising a program storage medium readable by a computer and embodying one or more instructions executable by the computer to perform a method for managing memory, the method comprising:

breaking up a file into two or more memory blocks;

managing the two or more memory blocks as nodes in a heap tree; ~~and wherein each node has a heap block reference;~~

~~independently compressing one or more of the two or more memory blocks without reprocessing the file.~~

~~receiving a request to access memory at a linear file address; and~~

~~translating the linear file address to an appropriate heap block reference to access the memory block.~~

17. (CURRENTLY AMENDED) The article of manufacture of claim 16, the method further comprising:

receiving a request to access memory at a linear file address; and  
translating the linear file address to an appropriate heap block reference to access the memory block, wherein the translating utilizes a file address mapping tree comprising a mapping from linear file addresses to heap block references.

18. (CURRENTLY AMENDED) The article of manufacture of claim 17+8, wherein the method further comprises updating the file address mapping tree when a block is inserted into the heap tree.

19. (ORIGINAL) The article of manufacture of claim 18, wherein the file address mapping tree is updated when address space is deleted by:

deleting an associated block from the heap tree;  
reducing a size of partial blocks as needed; and  
adjusting the file address mapping tree accordingly.

20. (CURRENTLY AMENDED) The article of manufacture of claim 18+6, wherein:

(a) the request to access memory comprises a request to insert data into the file at an insertion point; and

(b) the method further comprises:

- (i) breaking one of the memory blocks at the insertion point; and
- (ii) inserting the new data as a node in the heap tree.

21. (WITHDRAWN) An article of manufacture comprising a program storage medium readable by a computer and embodying one or more instructions executable by the computer to perform a method for allocating memory, the method comprising:

maintaining, in a tree, a tri-linked list of deallocated memory units available for use by a heap, wherein a first link points to available deallocated memory units smaller than a current block

size, a second link points to available deallocated memory units equal to the current block size, and a third link points to available deallocated memory units larger than the current block size;

receiving a request for memory;

traversing the tree to find a deallocated memory unit that satisfies the request for memory;

and

allocating the deallocated memory unit that satisfies the request.

22. (WITHDRAWN) The article of manufacture of claim 21, wherein the traversing does not search the second link.

23. (WITHDRAWN) The article of manufacture of claim 21, wherein memory units of equal size are linked together in the tree.